



sales@fitnessfloors.com
800-428-5306

Carpetile Sport™ Specifications

Material	Pile Fiber: 100% polypropylene
	Backing: Bitumen
Warranty	7 years on flat surfaces
Tile size	19.69" X 19.69"
Tile weight	2.57 ounces/tile
Tile height	.37"
Face weight	.80 ounces/tile
Case Quantity	20 tiles/case – 53.8 sf/case
Electrostatic Propensity	Permanently anti-static
Dimensional Stability (EN 986)	Pass
Walk on Test (ISO TR 6356)	< 2 KV (IBM/ICL)
Sound Insulation (ISO 14-B)	> or = 24 db
Thermal Retention (ISO 8302)	0.12m_KW
Coefficient of Friction	Wet-63; Dry-65
Radiant Panel Test (ASTM E648)	Pass
Pill Test (ASTM D2829)	Pass

Installation Instructions

- 1) Create center lines in both directions of the room and mark these center lines with a chalk line.
- 2) Adhesive should cover between 450-650 sf per gallon. Spread adhesive using a 1/8" X 1/8" X 1/16' V-notched trowel and only apply as much as can be worked with in a half hour period at a time. Allow the adhesive to set-up for 15 minutes before installing tiles.
- 3) Starting with the intersection of the chalk lines, install the first tile, aligning the tile with the vertical and horizontal lines. Work from the middle to the outside edges of the room. To lay the tiles in a parquet pattern, turn each tile one quarter from the orientation of the previous tile.
- 4) After tiles are completely laid, roll them in each direction with a 3-section 150 lb. roller.
- 5) Visually inspect the tiles to make sure that all tiles are flat and locked into place with no gaps between tiles.