

(Date)  
(Project)

General Disclaimer

While every effort has been made to ensure that the information contained within these specifications is comprehensive and accurate, Fitness Flooring, Inc. will not accept any liability for omissions or errors, and disclaim any and all liability that may be claimed arising out of reliance upon the information presented in these specifications. The user acknowledges that any reliance upon these specifications is at their sole risk and discretion. Fitness Flooring, Inc. has no obligation to correct any error or omission in any portion of these specifications.

Fitness Flooring, Inc. makes no representations concerning suitability or fitness for use of these specifications and expressly disclaim any and all warranties, express or implied, including without limitation warranties of suitability for a particular purpose.

**I Part One - General**

**1.01 RELATED SECTIONS**

*Spec Note: List appropriate Sections for related work specific to project*

*Refer to Manufacturers Installation Manual for complete information on receiving, installing, and maintaining Fitness Flooring DécorTile*

.A Section 15[ ] 16[ ]: Floor access covers, drains.

**1.02 REFERENCES**

- .A ASTM D2240, Rubber Property Durometer Hardness.
- .B ASTM D395, Rubber Property Compression Set Method B.
- .C ASTM C 501, Taber Abrasion.
- .D ASTM D412, Rubber Properties in Tension.
- .E ASTM C 1028, Co-Efficient of Friction.
- .F ASTM D624, Test Method for Rubber Properties.
- .G ASTM D 570, Moisture Absorption.
- .H ASTM E648-03, Critical Radiant Flux.
- .I ASTM F970-00, Static Load Limit
- .J ASTM E662, Optical Density of Smoke

**1.03 SUBMITTALS**

- .A Submit samples in accordance with Section [ ] - [ ].
- .B Submit duplicate 12 in. x 12 in. sample pieces of sheet material.
- .C Submit Material Safety Data Sheets for installation adhesives, cleaners and sealers.
- .D Submit layout drawing of flooring [tiles] to [Owner] [Consultant] [Engineer] for review prior to starting any work.

(Date)  
(Project)

**1.04 CLOSEOUT SUBMITTALS**

- .A Provide maintenance data for resilient flooring for incorporation into manual specified in Section [ ] – [ ].

**1.05 EXTRA MATERIALS**

- .A Provide extra materials of resilient sheet flooring and adhesives in accordance with Section [ ] – [ ].
- .B Provide [ ] sq. ft., [ %] of each [color], of flooring material required for project for maintenance use.
- .C Extra materials to be in one piece and from same production run as installed materials.
- .D Clearly identify each type of sheet flooring and each container of adhesive.
- .E Deliver to [Owner] [Architect], upon completion of the work of this section.
- .F Store where directed by [Owner] [Architect].

**1.06 DELIVERY, STORAGE AND HANDLING**

- .A Deliver flooring materials undamaged with manufacturer's labels intact.
- .B Store flooring materials in a protected area on site a minimum of 24 hours prior to installation.
- .C Store rubber flooring materials flat, blocked off floor.
- .D Prevent damage or contamination to flooring materials from water, moisture, freezing, excessive heat, direct sunlight and construction dust or dirt.
- .E Protect flooring materials from construction activities. Provide tarpaulins or plastic coverings blocked to allow ventilation and prevent contamination from dust or debris.

**1.07 ENVIRONMENTAL REQUIREMENTS**

- .A Maintain air temperature and structural base temperature at flooring installation area above 60 degrees F and below 85 degrees F for 48 hours before, during and 72 hours after installation.
- .B Maintain a maximum relative humidity of 65% before, during and for 72 hours after installation.

**1.08 WARRANTY**

- .A Supply manufacturer's standard limited warranty against defects in materials or workmanship for 5 years for Décor from date of purchase.
- .B Supply manufacturer's standard limited warranty against wear exceeding 1% per year when recommended installation and maintenance guidelines are followed.
- .C Warranty is void if solvent based adhesive is used for the installation of Décor tiles.







